Material Safety Data Sheet

Section 1 General Information

Manufacturer:

Zinsser Company, Inc. 173 Belmont Drive Somerset, NJ 08875 (732) 469-8100

Emergency Telepho	one: Chemtrec (800) 424-9300	Date: January 4, 2007
Product Name:	Parks Paint Thinner	

Codes: 002012 002015 002023

Section 2 Hazardous Ingredients

Hazardous Component	<u>CAS#</u>	OSHA <u>PEL</u>	ACGIH <u>TLV</u>
Stoddard Solvent	8052-41-3	500 ppm	100 ppm
1,3,5- Trimethyl Benzene	108-67-8	N.A.	25 ppm
1,2,4- Trimethyl Benzene	95-63-6	10 ppm (TWA) 25 ppm (Ceiling)	25 ppm
Xylene	1330-20-7	100 ppm	100 ppm 150 ppm-STEL
Ethylbenzene	100-41-4	100 ppm	100 ppm 100 ppm 125 ppm STEL

Section 3 Hazard Identification

Emergency Overview: This material is a colorless liquid with a characteristic kerosenelike odor. It is flammable and has a flash point of 105° F. The vapor is heavier than air and may travel along the ground. Ignition of the vapor by distant ignition sources is possible.

Primary Routes of Exposure:

Skin Contact Eye Contact Inhalation

Potential Acute Health Effects:

Eye: Contact may cause eye irritation.

Skin: May cause skin irritation. Repeated or prolonged contact with skin may cause dermatitis.

Ingestion: May be harmful if swallowed. This material may pose an aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. The substance may cause effects on the central nervous system. This substance may cause gastrointestinal tract distress and central nervous system depression.

Inhalation: High vapor concentrations may be irritating to the eyes, nose, throat and lungs.

Potential Chronic Health Effects: The substance may defat the skin. This substance may have effects on the central nervous system.

Target Organ: Eyes, skin, respiratory system, central nervous system, kidneys.

(See also Sections 4, 8, and 11 for related information) Signs and Symptoms: None known

(See also Sections 4, 8, and 11for related information)

Section 4 First Aid Measures

Eye contact: Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation persists.

Skin contact: Wash thoroughly with soap and water. Get medical attention if irritation develops or persists.

Ingestion: If swallowed, Contact a physician or Poison Control Center. This material may pose an aspiration hazard. Do Not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. The symptoms of chemical pneumonitis often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Section 5 Fire Fighting Measures

Flash Point (method): 105°F

Extinguishing Media: Foam, Dry Chemical, Water Fog, CO₂

Protection of Firefighters: As in any fire, wear self-contained breathing apparatus pressuredemand, NIOSH and full protective gear. Evacuate area and fight fire from safe distance.

LEL: 1.0% **UEL:** 6.0%

Section 6 Accidental Release Measures

Clean Up Methods: Eliminate all ignition sources. Keep unnecessary people away. Dike and contain spill with inert material (sand, earth, etc.). Transfer liquid to containers for recovery or disposal, or absorb with absorbent materials and place into containers for disposal. Keep spill out of sewer and open bodies of water. Floors may be slippery; care should be exercised to avoid falls during clean up operations.

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment)

Section 7 Handling and Storage

Handling: Keep away from heat, sparks and open flame. Use with adequate ventilation. Keep container closed. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected areas with water.

Storage: Keep away from heat, sparks and open flame. Keep container closed

Section 8 Exposure Controls / Personal Protection

Engineering Controls: Use in well-ventilated areas. If necessary use mechanical local exhaust ventilation or general room dilution ventilation to reduce vapor concentrations.

Personal Protective Equipment (PPE):

Eye Protection: Prevent eye contact. Wear chemical splash goggles or similar eye protection if the potential exists for eye contact.

Skin Protection: Prevent skin contact. Wear chemical-resistant flexible-type gloves (neoprene, PVC, butyl, nitrile or similar). Depending on conditions of use additional protective equipment may be necessary such as face-shield, apron or coveralls.

Respiratory Protection: None required for normally expected use conditions. If occupational exposure limits are exceeded or if irritation is experienced, wear an appropriate NIOSH approved respirator with organic vapor cartridges.

General Hygiene Practices: Wash after handling material. Prevent Eye contact. Avoid prolonged skin and inhalation contact. Wash thoroughly before handling food, cosmetics, or before smoking. Remove contaminated clothing and launder before reuse.

Section 9 Physical Data

Appearance: C	olorless liquid	Odor: Kerosene-like odor.
Physical State:	Liquid	pH: N/A
Boiling Point:	$310-405^\circ\ F$	Melting Point: N/D
Vapor Pressure: 2	mmHg	Vapor Density: 4.9
Odor Threshold:	N/D	Viscosity: N/D
Solubility in Water	: Negligible (<5%)	Specific Gravity: 0.78

Section 10 Stability and Reactivity

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products: Reacts with chloroform and bromoform under basic conditions, causing fire and explosion hazard.

Stability: Stable.

Incompatibility: Strong oxidizers. May react with strong oxidizer causing fire and explosion hazard. Attacks some forms of plastics, rubber, and coatings.

Section 11 Toxicological Information

Carcinogenicity: This material is not listed as a carcinogen by IARC, NTP or OSHA.

(See also Section 15 for related information)

Section 12 Ecological Information

Chemical Fate and Effects: None known

Section 13 Disposal Considerations

RCRA Hazardous Waste: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to characteristics of ignitability (D001). The transportation, storage, treatment, and disposal of this waste must be conducted in compliance with 40 CFR 262,263,264,268, and 270. Disposal can only occur in properly permitted facilities. Check state and local regulations for any additional requirements as these may be more restrictive than federal laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate.

Section 14 Transportation Information

Regulated by the DOT: Yes

DOT Proper Shipping Name: Paint Related Material

UN / NA Number: UN1263

Hazard Class: 3

Packing Group: III

Section 15 Regulatory Information

CERCLA:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a level which could require reporting under the statute are:

Chemical Name	CAS#	Maximum Concentration (Wt. %)
Xylene	1330-20-7	3.0 %
Ethylbenzene	100-41-4	1.0 %

SARA Title III, section 311/312:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 304, 311 and 312).

Components present in this product at a level which could require reporting under the statute are:

Chemical Name	CAS#	Maximum Concentration (Wt. %)
None	N/A	N/A

SARA Title III, section 313:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

Chemical Name	CAS#	Maximum Concentration (Wt. %)
1,2,4 Tri Methyl Benzene	95-63-6	6.0 %
Xylene	1330-20-7	3.0 %
Ethylbenzene	100-41-4	1.0 %

TSCA:

N/A: Not Applicable	N/D: Not Determined	N/E: Not Established	N/R: Not Required	Est.: Estimated
---------------------	---------------------	----------------------	-------------------	-----------------

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

This product does contain chemicals that require export notification under Section 12(b) of the TSCA regulation.

Chemical Name	CAS#	Maximum Concentration (Wt. %)
Xylene	1330-20-7	3.0 %

Section 16 Other Information

Legend:	N/A: Not Applicable	N/D: Not Determined	
-	N/E: Not Established	N/R: Not Required	
	cps: Centipoise	KU : Krebs Units	
	STEL: Short Term Exposure Limit	C: OSHA Ceiling Value	
	PPM : Parts Per Million	PPB : Parts Per Billion	
	PEL: Permissible Exposure Limit	TLV: Threshold Limit Value	
	TWA: Time Weighted Average	mg/m³ : Milligrams per cubic Meter	
	mppcf: Million particles per cubic foot of a	ir.	
	ACGIH: American Conference of Governme	mental Industrial Hygienists	
	OSHA : Occupational Safety and Health Ad	ministration (US Dept. of Labor)	
	RCRA: Resource Conservation and recover	ry Act	
	SARA: Superfund Amendment and Reauthorization Act		
	TSCA: Toxic Substance Control Act		
	FHSA: Federal Hazardous Substance Act		

Prepared By:Zinsser Health and Safety Manager, Regulatory Compliance Dept.173 Belmont DriveSomerset, NJ08875(732) 469-8100

Disclaimer: Zinsser Co., Inc. believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state, and local laws and regulations.