Permatex. Inc. 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex

(877) 376-2839

Emergency: 800-255-3924

International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: SURFACE INSENSITIVE THREADLOCKER BLUE 6ML

Item No: 24027 **Product Type: Anaerobic**

2. COMPOSITION/INFORMATION ON INGREDIENTS						
Component	Weight%	ACGIH TLV: TWA	OSHA PEL:			
POLYGLYCOL DIMETHACRYLATE 25852-47-5	50-70	Not listed	Not Listed			
TETRAETHYLENE GLYCOL HEXOATE 18268-70-7	10-20	Not listed	Not Listed			
POLYVINYL ACETATE 9003-20-7	<5	Not listed	Not Listed			
POLYETHYLENE HOMOPOLYMER 9002-88-4	<5	Not listed	Not Listed			
PROPYLENE GLYCOL 57-55-6	<5	Not listed	Not Listed			
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<2	Not listed	Not Listed			
SACCHARIN 81-07-2	<2	10mg/m ³ nuisance dust	Not Listed			
ACRYLIC ACID 79-10-7	0.1-1.0	2 ppm TWA	10 ppm TWA; 30 mg/m ³ TWA			

3. HAZARDS IDENTIFICATION

May cause eye and skin irritation. At elevated temperatures may cause irritation of the respiratory tract. **Toxicity:**

Irritates mucous membranes. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. High concentrations may cause central nervous system (CNS) depression. May cause skin

sensitization.

Primary Routes of Entry:

Eye and skin contact, ingestion, inhalation

Repeated skin contact may cause allergic skin reactions. Ingestion may cause nausea and vomiting. Signs and Symptoms of Exposure:

Inhalation overexposure may cause irritation, coughing and flu-like symptoms. May cause pain, redness

or swelling of the eyes and excessive blinking and tear production.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
POLYVINYL ACETATE	<5			Group 3: Vol.19, Supp 7;
9003-20-7				1987
SACCHARIN	<2	Delisted April 2000		Group 3: Vol 73, 1999
81-07-2				
ACRYLIC ACID	0.1-1.0		A4 - Not Classifiable	Group 3 Monograph 71,
79-10-7			as a Human	1999; Supplement 7, 1987;
			Carcinogen	Monograph 19, 1979

Medical Conditions Recognized as Being Aggravated by Exposure:

May aggrevate preexisting dermatitis.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

Wash off with soap and water. If skin irritation persists, call a physician. **Skin Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical **Eye Contact:**

attention if irritation persists.

Product Name: SURFACE INSENSITIVE <u>Item No:</u> 24027

THREADLOCKER BLUE 6ML

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): >200°F PMCC

Recommended Extinguishing Media: Water fog, carbon dioxide, foam, dry chemical.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.

Hazardous Products of Combustion: Oxides of carbon

Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat

Lower Explosive Limit: Not determined Upper Explosive Limit: Not determined Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until

disposal.

7. HANDLING AND STORAGE

Storage: Store below 100 degrees F.

Handling: Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eves: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure

limits (or to the lowest feasible levels when limits have not been established) during the use of this

product.

Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the

applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Odor:

Boiling Point:

pH:

Solubility in Water:

Specific Gravity:

VOC Content(Wt.%):

Blue liquid

MILD

>300°F

Does not apply

Insoluble

1.00-1.15

Vapor Pressure:
Vapor Density (Air=1):

Evaporation Rate:

Not determined
Heavier than air
Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: Will not occur.

Incompatabilities: Strong oxidizers, free radical initiators, inert gases, Peroxides

Conditions to Avoid: Heat

Hazardous Products of Combustion: Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

Product Name: SURFACE INSENSITIVE <u>Item No:</u> 24027

THREADLOCKER BLUE 6ML

14. TRANSPORTATION INFORMATION

DOT Shipping Name:
Hazard Class:
UN/ID Number:
Marine Pollutant:
Unrestricted
None
None

IATA

Proper Shipping Name: Not regulated

Class or Division: None UN/ID Number: None

IMDG

Proper Shipping: Unrestricted Hazard Class: None UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1.
Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety Revision Date: April/22/2008

Company: Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 06106 Revision

Number:

Telephone No.: 1-87-Permatex (877) 376-2839