

# SAFETY DATA SHEET

Creation Date 07-Sep-2010 Revision Date 18-Sep-2014 Revision Number 1

1. Identification

Product Name tert-Butanol

Cat No.: AC447010000, AC447010010, AC447010025

**Synonyms** tert-Butyl alcohol; 2-Methyl-2-propanol

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Entity / Business Name

Fisher Scientific Acros Organics
One Reagent Lane One Reagent Lane

Fair Lawn, NJ 07410 Fair Lawn, NJ 07410 Tel: (201) 796-7100

E

**Emergency Telephone Number** 

For information US call: 001-800-ACROS-01

/ Europe call: +32 14 57 52 11

Emergency Number **US:**001-201-796-7100 /

Europe: +32 14 57 52 99

CHEMTREC Tel. No.US:001-800-424-9300 /

Europe:001-703-527-3887

# 2. Hazard(s) identification

## Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute Inhalation Toxicity - Vapors

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Target Organs - Respiratory system, Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure)

Category 2

Category 2

Target Organs - Kidney, Liver.

## **Label Elements**

## Signal Word

Danger

## **Hazard Statements**

Highly flammable liquid and vapor Causes serious eye irritation Harmful if inhaled May cause respiratory irritation

May cause damage to organs through prolonged or repeated exposure

Revision Date 18-Sep-2014

tert-Butanol



# **Precautionary Statements**

#### Prevention

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

#### Response

Get medical attention/advice if you feel unwell

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

# Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

# Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None identified

# 3. Composition / information on ingredients

Component		CAS-No	Weight %	
	tert-Butyl alcohol	75-65-0	>95	

# 4. First-aid measures

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Obtain medical attention.

Ingestion Do not induce vomiting. Obtain medical attention.

Most important symptoms/effects

Breathing difficulties. . Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

**Notes to Physician** 

Treat symptomatically

# 5. Fire-fighting measures

**Suitable Extinguishing Media** 

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed

containers exposed to fire with water spray.

**Unsuitable Extinguishing Media** 

No information available

**Flash Point** Method -

11 °C / 51.8 °F No information available

**Autoignition Temperature** 

470 °C / 878 °F

**Explosion Limits** 

8.0 vol %

Upper Lower

2.4 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge

No information available

## Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO) Carbon dioxide (CO2)

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

## 6. Accidental release measures

**Personal Precautions** 

Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental Precautions** 

Should not be released into the environment. See Section 12 for additional ecological information.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

_						
7	ы٠	an	Ы	ina	and	storage
/ .	1 10	ап	uі	HIU	anu	Storage

Handling

Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal

parts of the equipment must be grounded.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat and sources of ignition.

# 8. Exposure controls / personal protection

**Exposure Guidelines** 

#### tert-Butanol

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
tert-Butyl alcohol	TWA: 100 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 300 mg/m³ (Vacated) STEL: 150 ppm (Vacated) STEL: 450 mg/m³ TWA: 100 ppm TWA: 300 mg/m³	IDLH: 1600 ppm TWA: 100 ppm TWA: 300 mg/m³ STEL: 150 ppm STEL: 450 mg/m³

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
tert-Butyl alcohol	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
	TWA: 303 mg/m <sup>3</sup>	TWA: 300 mg/m <sup>3</sup>	
	_	STEL: 150 ppm	
		STEL: 450 mg/m <sup>3</sup>	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations

and safety showers are close to the workstation location. Ensure adequate ventilation,

especially in confined areas.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

**Respiratory Protection** No protective equipment is needed under normal use conditions.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceClearOdorStrong

Odor Threshold No information available

Hq

 Melting Point/Range
 25 - 25.5 °C / 77 - 77.9 °F

 Boiling Point/Range
 83 °C / 181.4 °F @ 760 mmHg

Flash Point 11 °C / 51.8 °F

Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 8.0 vol %

 Lower
 2.4 vol %

 Vapor Pressure
 36 mbar @ 20 °C

 Vapor Density
 2.6 (Air = 1.0)

 Relative Density
 0.780

SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature470 °C / 878 °FDecomposition TemperatureNo information available

Viscosity 6.43 mPa.s (25°C)

Molecular FormulaC4 H10 OMolecular Weight74.12

tert-Butanol Revision Date 18-Sep-2014

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** May form explosive peroxides.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Alkali metals

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

# 11. Toxicological information

## **Acute Toxicity**

#### **Product Information**

**Component Information** 

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
tert-Butyl alcohol	>3100 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>31 mg/L/4h (Rat)		

**Toxicologically Synergistic** 

**Products** 

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and respiratory system

**Sensitization** No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ī	tert-Butyl alcohol	75-65-0	Not listed				

Mutagenic Effects No information available

Reproductive Effects No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure Kidney Liver

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed tiredn

**Endocrine Disruptor Information** 

tiredness, nausea and vomiting

No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

**Ecotoxicity** 

Do not empty into drains.

tert-Butanol Revision Date 18-Sep-2014

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
tert-Butyl alcohol	EC50 1000 mg/L 72 h	LC50 >961 mg/L/96h (Pimephales promelas)	EC50 > 10000 mg/L 17 h	EC50 933 mg/L 48 h

Persistence and Degradability

Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** 

No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

Component	log Pow
tert-Butyl alcohol	0.35

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

# 14. Transport information

DOT

UN-No UN1120 Proper Shipping Name BUTANOLS

Hazard Class 3 Packing Group II

TDG

UN-No UN1120
Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group

IATA

UN-No UN1120
Proper Shipping Name BUTANOLS

Hazard Class 3
Packing Group

IMDG/IMO

UN-No UN1120 Proper Shipping Name BUTANOLS

Hazard Class 3 Packing Group II

# 15. Regulatory information

#### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
tert-Butyl alcohol	Χ	Χ	-	200-889-7	-		Χ	Χ	Χ	Х	X

## Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

tert-Butanol Revision Date 18-Sep-2014

## U.S. Federal Regulations

TSCA 12(b) Not applicable

## **SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
tert-Butyl alcohol	75-65-0	>95	1.0

## SARA 311/312 Hazardous Categorization

Acute Health Hazard

Chronic Health Hazard

Fire Hazard

Sudden Release of Pressure Hazard

No
Reactive Hazard

Yes

Yes

Yes

No

Clean Water Act Not applicable

Clean Air Act Not applicable

**OSHA** Occupational Safety and Health Administration

Not applicable

#### **CERCLA**

Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals

# State Right-to-Know

Component Massachusetts		New Jersey	Pennsylvania	Illinois	Rhode Island
tert-Butyl alcohol	X	X	X	-	X

## **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

## **U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

# Other International Regulations

Mexico - Grade No information available

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid

D2B Toxic materials D1B Toxic materials



Revision Date 18-Sep-2014

# 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 07-Sep-2010

 Revision Date
 18-Sep-2014

 Print Date
 18-Sep-2014

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

## Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**