

# Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 1 of 9

## Copper, Granular, 50 Mesh,

### SECTION 1 : Identification of the substance/mixture and of the supplier

**Product name :** Copper, Granular, 50 Mesh,

**Manufacturer/Supplier Trade name:**

**Manufacturer/Supplier Article number: S25268**

**Recommended uses of the product and uses restrictions on use:**

**Manufacturer Details:**

AquaPhoenix Scientific  
9 Barnhart Drive, Hanover, PA 17331

**Supplier Details:**

Fisher Science Education  
15 Jet View Drive, Rochester, NY 14624

**Emergency telephone number:**

Fisher Science Education Emergency Telephone No.: 800-535-5053

### SECTION 2 : Hazards identification

**Classification of the substance or mixture:**



**Toxic**

Acute toxicity (oral, dermal, inhalation), category 2



**Irritant**

Eye irritation, category 2A  
Skin sensitization, category 1



**Health hazard**

Germ cell mutagenicity, category 1A  
Specific target organ toxicity following repeated exposure, category 2

Acute toxicity - Oral - Category 2: H300 Fatal if swallowed.

Acute toxicity - Inhalation - Category 2: H330 Fatal if inhaled.

Specific target organ toxicity - Repeated exposure - (Oral, Inhalation) - Category 2: H373 May cause damage to digestive system, hematopoietic system, kidneys, nose, respiratory system, and/or skin through prolonged or repeated exposure if inhaled

Hazards Not Otherwise Classified - Combustible Dust

Not classified for physical or health hazards under GHS.

Hazards Not Otherwise Classified - Combustible Dust

Serious Eye Damage/Eye Irritation - Category 2: H319 Causes serious eye irritation.

Skin sensitizers - Category 1: H317 May cause allergic skin reaction.

Germ cell mutagenicity - Category 1: H340 May cause genetic defects.

Hazardous to aquatic environment - acute hazard - Category 1: H400 Very toxic to aquatic life.

**Signal word :** Danger

**Hazard statements:**

Fatal if swallowed

Fatal if inhaled

# Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 2 of 9

## Copper, Granular, 50 Mesh,

May cause an allergic skin reaction  
Causes serious eye irritation  
May cause genetic defects  
May cause damage to organs through prolonged or repeated exposure  
Very toxic to aquatic life

### Precautionary statements:

If medical advice is needed, have product container or label at hand  
Keep out of reach of children  
Read label before use  
If medical advice is needed, have product container or label at hand  
Keep out of reach of children  
Read label before use  
Wash skin thoroughly after handling  
Avoid release to the environment  
Do not eat, drink or smoke when using this product  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Wear protective gloves/protective clothing/eye protection/face protection  
Avoid breathing dust/fume/gas/mist/vapours/spray  
Use only outdoors or in a well-ventilated area  
Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Wash contaminated clothing before reuse  
IF exposed or concerned: Get medical advice/attention  
Collect spillage  
Specific treatment (see supplemental first aid instructions on this label)  
Rinse mouth  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Immediately call a POISON CENTER or doctor/physician  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do.  
Continue rinsing  
If eye irritation persists get medical advice/attention  
IF ON SKIN: Wash with soap and water  
If skin irritation or a rash occurs: Get medical advice/attention  
Store locked up  
Dispose of contents and container as instructed in Section 13

### Combustible Dust Hazard: :

May form combustible dust concentrations in air (during processing).

### Combustible Dust Hazard: :

May form combustible dust concentrations in air (during processing).

### Other Non-GHS Classification:

#### WHMIS



# Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 3 of 9

## Copper, Granular, 50 Mesh,

### NFPA/HMIS



NFPA SCALE (0-4)

Health	2
Flammability	2
Physical Hazard	0
Personal Protection	X

HMIS RATINGS (0-4)

### SECTION 3 : Composition/information on ingredients

#### Ingredients:

CAS 7440-50-8

Copper

100 %

Percentages are by weight

### SECTION 4 : First aid measures

#### Description of first aid measures

**After inhalation:** Loosen clothing as necessary and position individual in a comfortable position. Move exposed to fresh air. Give artificial respiration if necessary. If breathing is difficult give oxygen. Get medical assistance if cough or other symptoms appear.

**After skin contact:** Rinse/flush exposed skin gently using soap and water for 15-20 minutes. Seek medical advice if discomfort or irritation persists.

**After eye contact:** Protect unexposed eye. Rinse/flush exposed eye(s) gently using water for 15-20 minutes. Remove contact lens(es) if able to do so during rinsing. Seek medical attention if irritation persists or if concerned.

**After swallowing:** Rinse mouth thoroughly. Do not induce vomiting. Have exposed individual drink sips of water. Seek medical attention if irritation, discomfort or vomiting persists. Never give anything by mouth to an unconscious person.

#### Most important symptoms and effects, both acute and delayed:

Irritation, Nausea, Headache, Shortness of breath.;

#### Indication of any immediate medical attention and special treatment needed:

If seeking medical attention, provide SDS document to physician. Physician should treat symptomatically.

### SECTION 5 : Firefighting measures

#### Extinguishing media

**Suitable extinguishing agents:** Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition. Use water, dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

**For safety reasons unsuitable extinguishing agents:** None identified.

#### Special hazards arising from the substance or mixture:

Oxides of copper. Combustion products may include carbon oxides or other toxic vapors. Thermal decomposition can lead to release of irritating gases and vapors. Dust can be an explosion hazard when exposed to heat or flame. Noncombustible solid in bulk form, but powdered form may ignite.

#### Advice for firefighters:

# Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 4 of 9

## Copper, Granular, 50 Mesh,

**Protective equipment:** Use NIOSH-approved respiratory protection/breathing apparatus.

**Additional information (precautions):** Move product containers away from fire or keep cool with water spray as a protective measure, where feasible. Use spark-proof tools and explosion-proof equipment. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Avoid inhaling gases, fumes, dust, mist, vapor, and aerosols. Avoid contact with skin, eyes, and clothing.

### SECTION 6 : Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Use spark-proof tools and explosion-proof equipment. Ensure that air-handling systems are operational. Ensure adequate ventilation.

#### Environmental precautions:

Prevent from reaching drains, sewer or waterway. Collect contaminated soil for characterization per Section 13. Should not be released into environment.

#### Methods and material for containment and cleaning up:

Keep in suitable closed containers for disposal. Wear protective eyewear, gloves, and clothing. Refer to Section 8. Always obey local regulations. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect solids in powder form using vacuum with (HEPA filter). Evacuate personnel to safe areas. Clean up spills immediately, observing precautions in the Protective Equipment section. Sweep up, then place into a suitable container for disposal. Avoid generating dusty conditions.

#### Reference to other sections:

### SECTION 7 : Handling and storage

#### Precautions for safe handling:

Minimize dust generation and accumulation. Follow good hygiene procedures when handling chemical materials. Refer to Section 8. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with eyes, skin, and clothing.

#### Conditions for safe storage, including any incompatibilities:

Store away from incompatible materials. Protect from freezing and physical damage. Keep away from food and beverages. Provide ventilation for containers. Avoid storage near extreme heat, ignition sources or open flame. Store in cool, dry conditions in well sealed containers. Store with like hazards

### SECTION 8 : Exposure controls/personal protection



#### Control Parameters:

7440-50-8 , Copper , OSHA PEL TWA (Total Dust) TWA 1 mg/m<sup>3</sup>  
7440-50-8, Copper, ACGIH TLV: 0.2 mg/m<sup>3</sup> TWA (fume); 1 mg/m<sup>3</sup> TWA (dusts and mists)  
7440-50-8, Copper, OSHA PEL: 0.1 mg/m<sup>3</sup> TWA (fume)

# Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 5 of 9

## Copper, Granular, 50 Mesh,

- Appropriate Engineering controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use/handling. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or dusts (total/respirable) below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use under a fume hood
- Respiratory protection:** Not required under normal conditions of use. Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. When necessary use NIOSH approved breathing equipment.
- Protection of skin:** Select glove material impermeable and resistant to the substance. Select glove material based on rates of diffusion and degradation. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Use proper glove removal technique without touching outer surface. Avoid skin contact with used gloves. Wear protective clothing.
- Eye protection:** Wear equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses or goggles are appropriate eye protection.
- General hygienic measures:** Perform routine housekeeping. Wash hands before breaks and at the end of work. Avoid contact with skin, eyes, and clothing. Before wearing wash contaminated clothing.

## SECTION 9 : Physical and chemical properties

<b>Appearance (physical state,color):</b>	Red to brown solid	<b>Explosion limit lower: Explosion limit upper:</b>	Not determined Not determined
<b>Odor:</b>	Odorless	<b>Vapor pressure:</b>	Not determined
<b>Odor threshold:</b>	Not determined	<b>Vapor density:</b>	Not determined
<b>pH-value:</b>	Not determined	<b>Relative density:</b>	Not determined
<b>Melting/Freezing point:</b>	1083°C (1981.4°F)	<b>Solubilities:</b>	Insoluble
<b>Boiling point/Boiling range:</b>	2595°C (4703°F)	<b>Partition coefficient (n-octanol/water):</b>	Not determined
<b>Flash point (closed cup):</b>	Not determined	<b>Auto/Self-ignition temperature:</b>	Not determined
<b>Evaporation rate:</b>	Not determined	<b>Decomposition temperature:</b>	Not determined
<b>Flammability (solid,gaseous):</b>	Not determined	<b>Viscosity:</b>	a. Kinematic: Not determined b. Dynamic: Not determined
<b>Density:</b> 8.94 (Water = 1)			

# Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 6 of 9

## Copper, Granular, 50 Mesh,

### SECTION 10 : Stability and reactivity

**Reactivity:** Stable at room temperature in closed containers under normal storage and handling conditions.

**Chemical stability:** Stable under normal conditions.

**Possible hazardous reactions:** None under normal processing

**Conditions to avoid:** Incompatible Materials. Dust formation. Moisture. Exposure to air.

**Incompatible materials:** Liquid copper explodes on contact with water. Reacts violently with ammonium nitrate, bromates, iodates, chlorates, ethylene oxide, hydrazoic acid, potassium oxide, dimethyl sulfoxide Page 3 of 4 CU4500 + trichloroacetic acid, hydrogen peroxide, sodium peroxide, sodium azide, sulfuric acid, hydrogen sulfide + air, and lead azide. Ignites on contact with chlorine, fluorine (above 121C), chlorine trifluoride, and hydrazinium nitrate (above 70C). Incompatible with 1-bromo-2-propyne, potassium dioxide, and acetylenic compounds.

**Hazardous decomposition products:** Oxides of copper.

### SECTION 11 : Toxicological information

<b>Acute Toxicity:</b>		
<b>Oral:</b>	7440-50-8	LD50, Rat 472mg/KG
<b>Chronic Toxicity:</b>		
<b>Oral:</b>	7440-50-8	Chronic copper poisoning is typified by hepatic cirrhosis, brain damage and demyelination, kidney defects, and copper deposition in the cornea as exemplified by humans with Wilson's disease. It has also been reported that copper poisoning has led to hemolytic anemia and accelerates arteriosclerosis.
<b>Corrosion Irritation:</b>		
<b>Dermal:</b>	7440-50-8	Dust is irritating to the respiratory tract. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count.
<b>Sensitization:</b>		No additional information.
<b>Single Target Organ (STOT):</b>		No additional information.
<b>Numerical Measures:</b>		No additional information.
<b>Carcinogenicity:</b>		No additional information.
<b>Mutagenicity:</b>		Please refer to RTECS# BO9000000 for specific informaton.
<b>Reproductive Toxicity:</b>		Fertility: Post-implantation mortality, oral-rat TDLo=40mg/kg.

### SECTION 12 : Ecological information

#### Ecotoxicity

**Freshwater fish:** 96 Hr LC50 Pimephales promelas: 0.0068 - 0.0156 mg/L; 96 Hr LC50 Pimephales promelas:

# Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 7 of 9

## Copper, Granular, 50 Mesh,

<0.3 mg/L [static]; 96 Hr LC50 Pimephales promelas: 0.2 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 0.052 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 1.25 mg/L [static]; 96 Hr LC50 Cyprinus carpio: 0.3 mg/L [semi-static]; 96 Hr LC50 Cyprinus carpio: 0.8 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 0.112 mg/L [flow-through]

**Water flea:** 48 Hr EC50 Daphnia magna: 0.03 mg/L [Static]

**Persistence and degradability:** No information available.

**Bioaccumulative potential:** No information available.

**Mobility in soil:**

**Other adverse effects:** No information available.

### SECTION 13 : Disposal considerations

#### Waste disposal recommendations:

Contact a licensed professional waste disposal service to dispose of this material. Dispose of empty containers as unused product. Product or containers must not be disposed with household garbage. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities (US 40CFR262.11). Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations. Ensure complete and accurate classification.

### SECTION 14 : Transport information

#### UN-Number

3089

#### UN proper shipping name

Metal Powder, Flammable, NOS (Copper Sulfate)

#### Transport hazard class(es)



#### Class:

4.1 Flammable solids, self-reactive substances and solid desensitized explosives

**Packing group:** II

**Environmental hazard:**

**Transport in bulk:**

**Special precautions for user:**

### SECTION 15 : Regulatory information

#### United States (USA)

##### SARA Section 311/312 (Specific toxic chemical listings):

Acute, Chronic, Fire

##### SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed

##### RCRA (hazardous waste code):

None of the ingredients is listed

##### TSCA (Toxic Substances Control Act):

All ingredients are listed.

##### CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act):

7440-50-8 Copper Sulfate 5000 Lbs

## Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

Effective date : 03.02.2015

Page 8 of 9

### Copper, Granular, 50 Mesh,

#### Proposition 65 (California):

**Chemicals known to cause cancer:**

None of the ingredients is listed

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed

**Chemicals known to cause developmental toxicity:**

None of the ingredients is listed

#### Canada

**Canadian Domestic Substances List (DSL):**

All ingredients are listed.

**Canadian NPRI Ingredient Disclosure list (limit 0.1%):**

None of the ingredients is listed

**Canadian NPRI Ingredient Disclosure list (limit 1%):**

None of the ingredients is listed

#### SECTION 16 : Other information

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations. Note: The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the user to comply with all applicable laws and regulations applicable to this material.

#### GHS Full Text Phrases:

#### Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

PNEC: Predicted No-Effect Concentration (REACH)

CFR: Code of Federal Regulations (USA)

SARA: Superfund Amendments and Reauthorization Act (USA)

RCRA: Resource Conservation and Recovery Act (USA)

TSCA: Toxic Substances Control Act (USA)

NPRI: National Pollutant Release Inventory (Canada)

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)



## Safety Data Sheet

according to 29CFR1910/1200 and GHS Rev. 3

**Effective date** : 03.02.2015

Page 9 of 9

**Copper, Granular, 50 Mesh,**

**Effective date** : 03.02.2015

**Last updated** : 03.19.2015