

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : Fehling's Solution B, Alkaline No. 2
Product code : LC14210

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For laboratory and manufacturing use only.
Recommended use : Laboratory chemicals
Restrictions on use : Not for food, drug or household use

1.3. Supplier

LabChem, Inc.
1010 Jackson's Pointe Ct.
Zelienople, PA 16063 - USA
T 412-826-5230 - F 724-473-0647
info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or +1-703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 1 H314 Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage
Precautionary statements (GHS US) : P260 - Do not breathe mist, spray, vapors.
P264 - Wash exposed skin thoroughly after handling.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor/physician.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to comply with local, state and federal regulations.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : None.

2.4. Unknown acute toxicity (GHS US)

Not applicable

Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Water	(CAS-No.) 7732-18-5	60.9	Not classified
Sodium Potassium Tartrate, Tetrahydrate	(CAS-No.) 6381-59-5	34.6	Not classified
Sodium Hydroxide	(CAS-No.) 1310-73-2	4.5	Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: Corrosion of the upper respiratory tract.
Symptoms/effects after skin contact	: Caustic burns/corrosion of the skin. Blisters. Destruction of tissue.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Bleeding of the gastrointestinal tract. Burns to the gastric/intestinal mucosa. Diarrhoea. Nausea. Vomiting.
Symptoms/effects upon intravenous administration	: Not available.
Chronic symptoms	: No specific information available.

4.3. Immediate medical attention and special treatment, if necessary

Obtain medical assistance.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Not flammable.
Explosion hazard	: Not applicable.
Reactivity in case of fire	: Thermal decomposition generates : Corrosive vapors.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Complete protective clothing. Self-contained breathing apparatus.

Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Dike and contain spill.

6.1.1. For non-emergency personnel

Protective equipment : Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist, spray, vapors. Avoid contact during pregnancy/while nursing.

Hygiene measures : Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : incompatible materials. Keep container closed when not in use.

Incompatible products : metals. Strong acids.

Incompatible materials : Direct sunlight.

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: strong acids. metal powders. metals.

Packaging materials : MATERIAL TO AVOID: aluminium, tin, zinc.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Fehling's Solution B, Alkaline No. 2	
No additional information available	
Sodium Hydroxide (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA - IDLH - Occupational Exposure Limits	
US IDLH (mg/m ³)	10 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
Water (7732-18-5)	
No additional information available	
Sodium Potassium Tartrate, Tetrahydrate (6381-59-5)	
No additional information available	

Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Safety glasses. Chemical resistant apron.

Materials for protective clothing:

GIVE GOOD RESISTANCE: natural rubber. Latex gloves

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Respiratory protection not required in normal conditions

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: Odorless
Odor threshold	: No data available
pH	: ≥ 14
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.08 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available

Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: No data available.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts exothermically with (some) acids: release of (carbon dioxide).

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong oxidizers.

10.6. Hazardous decomposition products

Sodium oxide. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns. pH: ≥ 14
Serious eye damage/irritation	: Causes serious eye damage. pH: ≥ 14
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Skin and eye contact.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: Corrosion of the upper respiratory tract.
Symptoms/effects after skin contact	: Caustic burns/corrosion of the skin. Blisters. Destruction of tissue.

Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Bleeding of the gastrointestinal tract. Burns to the gastric/intestinal mucosa. Diarrhoea. Nausea. Vomiting.
Symptoms/effects upon intravenous administration	: Not available.
Chronic symptoms	: No specific information available.

SECTION 12: Ecological information

12.1. Toxicity

Sodium Hydroxide (1310-73-2)	
LC50 fish 1	45.4 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Solution >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h, Ceriodaphnia sp., Experimental value, Nominal concentration)

12.2. Persistence and degradability

Fehling's Solution B, Alkaline No. 2	
Persistence and degradability	Not established.
Sodium Hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
Water (7732-18-5)	
Persistence and degradability	Not established.
Sodium Potassium Tartrate, Tetrahydrate (6381-59-5)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Fehling's Solution B, Alkaline No. 2	
Bioaccumulative potential	Not established.
Sodium Hydroxide (1310-73-2)	
Bioaccumulative potential	Not bioaccumulative.
Water (7732-18-5)	
Bioaccumulative potential	Not established.
Sodium Potassium Tartrate, Tetrahydrate (6381-59-5)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Sodium Hydroxide (1310-73-2)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with local, state and federal regulations.
Ecology - waste materials	: Avoid release to the environment.

Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1824 Sodium hydroxide solution, 8, II
UN-No.(DOT)	: UN1824
Proper Shipping Name (DOT)	: Sodium hydroxide solution
Transport hazard class(es) (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 52 - Stow "separated from" acids
Other information	: No supplementary information available.

Transportation of Dangerous Goods

Transport document description	: UN1824 SODIUM HYDROXIDE SOLUTION, 8, II
UN-No. (TDG)	: UN1824
Proper Shipping Name (Transportation of Dangerous Goods)	: SODIUM HYDROXIDE SOLUTION
TDG Primary Hazard Classes	: 8 - Class 8 - Corrosives
Packing group	: II - Medium Danger
Explosive Limit and Limited Quantity Index	: 1 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 1 L

Transport by sea

Transport document description (IMDG)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, II
UN-No. (IMDG)	: 1824
Proper Shipping Name (IMDG)	: SODIUM HYDROXIDE SOLUTION
Class (IMDG)	: 8 - Corrosive substances

Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (IMDG) : II - substances presenting medium danger

Air transport

Transport document description (IATA) : UN 1824 Sodium hydroxide solution, 8, II
UN-No. (IATA) : 1824
Proper Shipping Name (IATA) : Sodium hydroxide solution
Class (IATA) : 8 - Corrosives
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Fehling's Solution B, Alkaline No. 2

SARA Section 311/312 Hazard Classes	Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Sodium Hydroxide (1310-73-2)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

15.2. International regulations

CANADA

Sodium Hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

Sodium Potassium Tartrate, Tetrahydrate (6381-59-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Revision date : 07/14/2020

Other information : None.

Full text of H-phrases: see section 16:

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Fehling's Solution B, Alkaline No. 2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : C

C - Safety glasses, Gloves, Synthetic apron

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.