

1. Identification

Product identifier Dykem® Remover & Prep (Bulk)

Other means of identification

Part Number 82638, 82738, 82838, 82938

Synonyms FORMULA CODE(S): * 8947

Recommended use Remover and cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway
Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2

Health hazards Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|------------------|--------------------------|------------|---------|
| Acetone | | 67-64-1 | 60 - 70 |
| Ethanol | | 64-17-5 | 30 - 40 |
| Isopropanol | | 67-63-0 | 1 - 5 |
| N-Propyl acetate | | 109-60-4 | 1 - 5 |

4. First-aid measures

| | |
|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Skin contact | Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed. |
| General information | Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media | Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Highly flammable liquid and vapor. |

6. Accidental release measures

| | |
|----------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| Environmental precautions | Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|---------------------------------|------|------------------------------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m ³ 1000 ppm |
| Ethanol (CAS 64-17-5) | PEL | 1900 mg/m ³ 1000 ppm |
| Isopropanol (CAS 67-63-0) | PEL | 980 mg/m ³ 400 ppm |
| N-Propyl acetate (CAS 109-60-4) | PEL | 840 mg/m ³ 200 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|---------------------------------|-------------|--------------------|
| Acetone (CAS 67-64-1) | STEL TWA | 500 ppm 250 ppm |
| Ethanol (CAS 64-17-5) | STEL | 1000 ppm |
| Isopropanol (CAS 67-63-0) | STEL TWA | 400 ppm 200 ppm |
| N-Propyl acetate (CAS 109-60-4) | STEL TWA | 250 ppm 200 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|---------------------------------|-------------|-----------------------------------------------------------------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m ³ 250 ppm |
| Ethanol (CAS 64-17-5) | TWA | 1900 mg/m ³ 1000 ppm |
| Isopropanol (CAS 67-63-0) | STEL TWA | 1225 mg/m ³ 500 ppm 980 mg/m ³ 400 ppm |
| N-Propyl acetate (CAS 109-60-4) | STEL TWA | 1050 mg/m ³ 250 ppm 840 mg/m ³ 200 ppm |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------|---------|-------------|----------|---------------|
| Acetone (CAS 67-64-1) | 25 mg/l | Acetone | Urine | * |

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|------------|-------|-------------|----------|---------------|
|------------|-------|-------------|----------|---------------|

| | | | | |
|---------------------------|---------|---------|-------|---|
| Isopropanol (CAS 67-63-0) | 40 mg/l | Acetone | Urine | * |
|---------------------------|---------|---------|-------|---|

* - For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Liquid.

Color

Clear.

Odor

Solvent.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

132.98 °F (56.1 °C)

Flash point

133.0 °F (56.1 °C) Tag Closed Cup

Evaporation rate

> 1 (BuAc = 1)

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)**

1.7 %

Flammability limit - upper (%)

21.2 %

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Not available.

Vapor density

> 1 (air = 1)

Relative density

0.79 @ 21.1°C

Solubility(ies)**Solubility (water)**

Completely soluble

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

| | |
|--------------------------|-------------------|
| Viscosity | Water thin |
| Other information | |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |
| VOC | 36.23 % ; 287 g/l |

10. Stability and reactivity

| | |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Acids. Strong oxidizing agents. |
| Hazardous decomposition products | Carbon oxides. |

11. Toxicological information

Information on likely routes of exposure

| | |
|--------------|------------------------------------------------------------------------------------------------------|
| Inhalation | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Causes serious eye irritation. |
| Ingestion | Expected to be a low ingestion hazard. |

Symptoms related to the physical, chemical and toxicological characteristics
 May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

Information on toxicological effects

Acute toxicity Not known.

| Components | Species | Test Results |
|------------|---------|--------------|
|------------|---------|--------------|

Ethanol (CAS 64-17-5)

Acute

Oral

| | | |
|------|-----|-------------------|
| LD50 | Rat | 1187 - 2769 mg/kg |
|------|-----|-------------------|

Isopropanol (CAS 67-63-0)

Acute

Oral

| | | |
|------|-----|----------|
| LD50 | Rat | 4.7 g/kg |
|------|-----|----------|

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

| | |
|-----------------------|--------------------------------------------|
| Acetone (CAS 67-64-1) | A4 Not classifiable as a human carcinogen. |
|-----------------------|--------------------------------------------|

| | |
|---------------------------|--------------------------------------------|
| Isopropanol (CAS 67-63-0) | A4 Not classifiable as a human carcinogen. |
|---------------------------|--------------------------------------------|

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

| | |
|-----------------------------------------------------------|--------------------------------------|
| Reproductive toxicity | Possible reproductive hazard. |
| Specific target organ toxicity - single exposure | May cause drowsiness and dizziness. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Prolonged inhalation may be harmful. |
| Further information | Symptoms may be delayed. |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | | Species | Test Results |
|---------------------------------|------|-----------------------------------------------------|------------------------------|
| Acetone (CAS 67-64-1) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 10294 - 17704 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| Ethanol (CAS 64-17-5) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 7.7 - 11.2 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | > 100 mg/l, 96 hours |
| Isopropanol (CAS 67-63-0) | | | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | > 1400 mg/l, 96 hours |
| N-Propyl acetate (CAS 109-60-4) | | | |
| Aquatic | | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 56 - 64 mg/l, 96 hours |

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|------------------|-------|
| Acetone | -0.24 |
| Ethanol | -0.31 |
| Isopropanol | 0.05 |
| N-Propyl acetate | 1.23 |

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

| | |
|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOT | |
| UN number | UN1263 |
| UN proper shipping name | Paint related material including paint thinning, drying, removing, or reducing compound |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | II |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | 149, B52, IB2, T4, TP1, TP8, TP28 |
| Packaging exceptions | 150 |
| Packaging non bulk | 173 |
| Packaging bulk | 242 |
| IATA | |
| UN number | UN1263 |
| UN proper shipping name | Paint related material (including paint thinning or reducing compounds) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | II |
| Environmental hazards | No. |
| ERG Code | 3L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed with restrictions. |
| Cargo aircraft only | Allowed with restrictions. |
| IMDG | |
| UN number | UN1263 |
| UN proper shipping name | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | II |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | F-E, <u>S</u> -E |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established. |

DOT





General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1) Low priority

Ethanol (CAS 64-17-5) Low priority

Isopropanol (CAS 67-63-0) Low priority

N-Propyl acetate (CAS 109-60-4) Low priority

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Ethanol (CAS 64-17-5)

Isopropanol (CAS 67-63-0)

N-Propyl acetate (CAS 109-60-4)

California Proposition 65



WARNING: California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Isopropanol (CAS 67-63-0)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|------------------------------------------------------------------------|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Toxic Chemical Substances (TCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 02-26-2018

Version # 01

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.